



ATX LED Consultants Inc
 1108 Lavaca Ste 110 #489
 Austin Tx, 78701
 512 377 6052
<http://atx-led.com>

MR16 LED Lights
Low Voltage 48 vdc
Dimmable

MR16 series

Bright LEDs, Cool Operation



AL-GU10
 GU10 base

AL-MR16
 G5.3 base

[Technical specifications](#)

Style	Watts	Volts	Current	lm	Note	Color
AL-GU10-48v5w-3500K	5	44-52 120*	0 – 110 mA 5 mA*	540	20 in parallel max	3500K CRI90
AL-GU10-48v5w-5000K	5	44-52 120*	0 – 110mA 5 mA*	400	20 in parallel max	5000K CRI90
AL-MR16-48v5w-3500K	5	44-52	0 – 110mA	400	20 in parallel max	3500K CRI90

* intended for safe operation in legacy power fixtures

Operating Concept

These devices allow parallel wiring as in conventional track lights, and allow dimming down to 5%. The dimming voltage is from 32 to 44 volts, from 44 to 52 volts the current (and lumens) are constant.

In the GU10 model, above 56v the current drops, reaching 5 mA at 120 volts. 120 Volt operation is not recommended, it is intended to allow safe interchange with exiting GU10 fixtures.

Use a simple on/off switch, or use a dimmer like the AL-WS-DR1 for dimming of up to 6 bulbs, a AL-WS-DR2 for 12 bulbs, or a SRP-2305-75 for up to 15 bulbs, or a ELG-150-48DA for 20 bulbs.



Typical GU10 fixture

